

HL 2001

6W, 8W, 13W
21W, 28W



- Operation Voltage:
220-240V / 50-60Hz



HL 2002

8W, 13W
21W, 28W



- Operation Voltage:
220-240V / 50-60Hz



HL 2003

13W, 21W



- Operation Voltage:
220-240V / 50-60Hz



HL 2004A

8W, 12W
16W, 20W



- Operation Voltage:
220-240V / 50-60Hz



HL 2004B

8W, 12W
16W, 20W



- Operation Voltage:
220-240V / 50-60Hz



HL 2004

8W
13W



- Operation Voltage:
220-240V / 50-60Hz



HL 2005

8W
13W



- Operation Voltage:
220-240V / 50-60Hz



HL 2006

8W, 13W



- Operation Voltage:
220-240V / 50-60Hz



HL 2008

8W
13W



- Operation Voltage:
220-240V / 50-60Hz



HL 3011

10W, 15W, 18W
30W, 36W



- Operation Voltage:
220-240V / 50-60Hz



HL 3013

10W, 15W, 18W
30W, 36W



- Operation Voltage:
220-240V / 50-60Hz



HL 3017

2x18W
2x36W



- Operation Voltage:
220-240V / 50-60Hz



HL 2010

8W
13W



- Operation Voltage:
220-240V / 50-60Hz



HL 3016

10W, 15W, 18W
30W, 36W



- Operation Voltage:
220-240V / 50-60Hz



HL 3013R

18W
36W



- Operation Voltage:
220-240V / 50-60Hz



HL 3017R

2x18W
2x36W



- Operation Voltage:
220-240V / 50-60Hz



HL 3020

10W, 15W, 18W
30W, 36W



- Operation Voltage:
220-240V / 50-60Hz



HL 3030

10W, 15W, 18W
30W, 36W



- Operation Voltage:
220-240V / 50-60Hz



HL 3021

11W



- Operation Voltage:
220-240V / 50-60Hz



HL 160 18W

HL 163 2x36W



- Operation Voltage:
220-240V / 50-60Hz



HL 161 36W

HL 165 36W



- Operation Voltage:
220-240V / 50-60Hz



HL 2007

- CAR PLUG OR EURO PLUG
- 5m CABLE
- 8W



- Operation Voltage:
220-240V / 50-60Hz



HL 150

- Operation Voltage: 220-240V / 50-60Hz
- With built-in suitable ballast & starter
- Current: 0.37A
- ΔT65°C TW105°
- Max 20W

**HL 152**

- Operation Voltage: 220-240V / 50-60Hz
- With built-in suitable ballast & starter
- Current: 0.43A
- ΔT65°C TW105°
- Max 40W

**HL 151**

- Operation Voltage: 220-240V / 50-60Hz
- With built-in suitable ballast & starter
- Current: 0.41A
- ΔT65°C TW105°
- Max 2x20W

**HL 153**

- Operation Voltage: 220-240V / 50-60Hz
- With built-in suitable ballast & starter
- Current: 0.43A
- ΔT65°C TW105°
- Max 2x40W

